RackView Fold Forward



Features and Benefits

- The following model features are available:
- 1U 15" / 17" TFT/LCD high-resolution monitor
- 2U 15" / 19" / 20" TFT/LCD high-resolution monitor
- Tactile keyboard with separate numeric keypad
- 1600 x 1200 @ 75Hz resolution on the 20" model
- Integrated trackball or touchpad mouse
- PS/2 or USB connections
- Built-in single or multiple user KVM switch options provides access to as many as 1,000 computers
- Quick and easy rack mounting installation
- Supports AT/XT, PS/2, and UNIX computers
- Front panel conceals unit when it is not in use
- Full size keyboard for typing in comfort
- Keyboard available in international variations
- Monitor OSD allows for easy adjustments of color, brightness, contrast, position, and shape of the display
- Front panel controls for quick adjustments
- Easy-glide KVM drawer can be mounted at any height in a standard 19 inch rack

Rack mounted KVM Station with KVM switch option

Optional single or multiple user KVM switch

20" model resolution up to 1600 x 1200 @ 75Hz

1U or 2U models available in 15", 17", 19", or 20" LCD versions

the 2U, 15" model is available in three versions:

- 1- 15" LCD monitor / 18" deep
- 2- 15" LCD monitor / 20" deep
- 3- 15" LCD monitor / 24" deep

High-resolution Trackball or Touchpad mouse

PS/2 or USB connectors

Compatible with PC's, UNIX, Sun, and Mac

The RackView[™] Advantage . . .

The RackView offers the latest, most efficient way to organize and streamline your server rooms and multiple computers. The RackView is a rack mountable KVM station neatly fitted in a 1U or 2U compact pull-out drawer. This easy-glide KVM station contains a high-resolution TFT/LCD monitor, a tactile keyboard, and a high-resolution trackball or touchpad mouse.

The RackView can be placed at any height within a standard 19" rack. This offers the operator the maximum in comfort and takes up a minimum amount of rack space.

The front panel conceals the unit when it is not in use.

The optional KVM switch offers single or multiple user access to as many as 1,000 servers or computers. Rose Electronics KVM switch options are fully expandable and when combined with the RackView, your system becomes a versatile, distributed matrix controlled system with multi-user capability, controlled access to the servers, and many other features.

PC's, UNIX, Sun, and Apple computers can easily be accessed, monitored, and controlled locally using RackView.



Easy access right at the rack



Typical Application



Introduction The RackView is the perfect addition to your server room. It mounts easily at any height in a standard 19" rack. It takes up 85% less space than a standard keyboard, monitor, and mouse and slides easily into the rack and out of site when it's not in use. The optional built-in KVM switch capability offers the added convenience of complete access to as many as 1,000 servers or computers. Adding a multi-user KVM switch allows server management to be performed locally from RackView or remotely from multiple KVM workstations.

Installation RackView is very easy to install. Simply adjust the rack rail length to the depth of your rack, slide the unit through the rack, and secure the rack mount brackets to the rack rails.

Front Panel The monitor's front panel has easy access switches which set the brightness, contrast, and invoke the On-Screen-Display. The OSD provides for an easy way to adjust all the monitors' parameters.

Keyboard The RackView's tactile keyboard is a full size keyboard with a separate numeric keypad. The keyboard is available with a PS/2, MiniDIN6 connector or USB.

Mouse The RackView has a high-resolution Trackball with a PS/2 or USB connector or Touchpad, depending on the model.

Monitor The high resolution, static free, TFT/LCD color monitor provides a crisp, clear image with resolutions up to 1280 x 1024 @ 75Hz. (20" model - 1600 x 1200 @ 75Hz)

Options The RackView can be ordered with an optional KVM switch. It is recommended that the KVM switch be a 1U high, 1×4 , 1×8 , 2×4 , or a 2×8 model.

Part Numbers	Description (PS/2 or USB)			
RV1-CKVM15E	1U KVM Drawer, 15" LCD, Trackball			
RV1-CKVM17E	1U KVM Drawer, 17" LCD, Trackball			
RV1-CKVM19E	1U KVM Drawer, 19" LCD, Trackball			
RV2-CKVM19E	2U KVM Drawer, 19" LCD, Trackball			
RV2-CKVM20E	2U KVM Drawer, 20" LCD, Trackball			
RV1-CKVT15E	1U KVM Drawer, 15" LCD, Touchpad			
RV1-CKVT17E	1U KVM Drawer, 17" LCD, Touchpad			
RV1-CKVT19E	1U KVM Drawer, 19" LCD, Touchpad			
RV2-CKVT19E	2U KVM Drawer, 19" LCD, Touchpad			
RV2-CKVT20E	2U KVM Drawer, 20" LCD, Touchpad			
RV2-CKVM15E-18	2U VKM Drawer, 15" LCD, Touchpad			
	(18" deep)			

/U part number suffix = USB **Specifications**

Dimensions	Depth	Min with	Weight
	Min Max	Switch	
15" models	26.0" – 36.0"	29″	28lbs
17" models	26.0" – 36.0"	29″	28lbs
18" deep model	18.0" – 23.0"	N/A	28lbs
15" 2U model	24.0" – 34.0"	29″	
19" / 20" 2U model	28.0" – 39.0"	32"	

	Resolution	15″ 1024 x 768 @ 75Hz 17″ / 19″ 1280 x 1024 @ 75Hz 20″ 1600 x 1200 @ 75Hz	
	Colors:	16.7 million	
	Controls:	Front panel	
	Adjustments:	On-Screen-Display	
	Keyboard: numeric keypa	Full size tactile keyboard with separate	
	Mouse:	Trackball or Touchpad	
	Connectors:	Video: HD15F Keyboard: PS/2 or USB Mouse: PS/2 or USB	
	Power adapter	100-240 VAC 50/60 Hz in / +12VDC, 5A out	
Environmental 32°F - 122°F (0°- 50° C),			

Environmental 32°F - 122°F (0°- 50° C), 20%-80% non-condensing RH



RackView with optional KVM switch

■ Phone: 281-933-7673 ■ E-mail: sales@rose.com ■ 10707 Stancliff Rd. Houston, TX 77099 Rose Electronics – Europe: +49 (0)2454 969442 Rose Electronics – Asia: +65 6324 2322



© Copyright Rose Electronics 2004. All rights reserved